



CXX955-11	CXX939
ENGINE	
Weichai /Steyer Wd615 67g-28 Diesel Engine	Weichai /Deutz TD226B-6G Diesel Engine
Net rated power: 163kW @ 2200rpm	Net rated power: 92kW @ 2200rpm
TRANSMISSION	
Countershaft-type power shift	Countershaft-type power shift
AXLES	
Brakes: Dry disc	Brakes: Dry disc
TIPPING LOAD	
Straight: 11 775 kg Full Turn 10 490 kg	Straight: 8 684 kg Full Turn 7 360 kg
BUCKET CAPACITY	
Heaped: 3.3m <sup>3</sup>	Heaped: 2.0m <sup>3</sup>
TARE	
Standard: 15 700 kg	Standard: 9 700 kg
TYRES	
23.5 x 25 L3 16 Ply	7.5 x 25 L3 16 Ply
BREAKOUT FORCE	
14 500 kg	9 700 kg

# LOADER MODELS

Specialisation in service levels and skills; knowledge of the machine, spare parts and support, lead to a decision to specialise in two models: a 10 ton and a 16 ton. The machines are simple but very reliable. The basic mechanic will be able to service and repair the machine. Machines are SABS approved and air conditioning is optional.

The 3m<sup>3</sup> is available at the factory with Cummins or Cat engines, but a decision was taken to equip all machines with a Wiechai WD 615 engine. As a result there are many satisfied customers due to the excellent diesel consumption of approximately 12 litres per hour. Certain models of truck in South Africa are also equipped with this engine. The transmission is a winner. It consists only of a working gear, a driving gear and a reverse gear.

“KEEP-IT-SIMPLE” – NO COMPUTERS!



WORKSHOP TEAM consists of 3 qualified mechanics who are at your service 24 hours a day, 7 days a week, to ensure clients of phenomenal service at all times!

You are assured SPARE PARTS, in stock at all times. Not one clients' machine has ever been down for longer than 48 hours due to lacking spare parts in stock or failure to repair their machine. The spare parts are very reasonably priced and a comprehensive store is available at all times.



## HOUSE OF BUILDING PLANT & TOOLS

contact **Neels Barnard @ 083 262 0892**  
 Plot 68, Church Street, Pelindaba  
[neelsbarnard@mweb.co.za](mailto:neelsbarnard@mweb.co.za)

